SAFETY DATA SHEET

KELLY-MOORE PAINTS The Painter's Paint Store

1. Identification

Product identifier	1250 AcryShield Exterior Semi-Gloss Stoc	k Colors 23 407 417
Other means of identification		
Product code	1250-23, 1250-407, 1250-417	
Recommended use	Architectural Coating	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier	/Distributor information	
Company name	Kelly-Moore Paint Co., Inc.	
Address	987 Commercial St., San Carlos, CA 94070	
Telephone	1-800-874-4436	
E-mail	TAlvarez@kellymoore.com	
Contact person	Tiffany Alvarez Gonda	
Emergency phone number	CHEMTREC: 1-800-424-9300	
2. Hazard(s) identification		
Physical hazards	Not classified.	
Health hazards	Sensitization, skin	Category 1
OSHA defined hazards	Not classified.	



	▼
Signal word	Warning
Hazard statement	May cause an allergic skin reaction.
Precautionary statement	
Prevention	Avoid breathing mist/vapor. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves.
Response	If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Storage	Store away from incompatible materials.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Label elements

Chemical name	CAS number	%
Titanium dioxide	13463-67-7	< 21
Carbon black	1333-86-4	< 2
4,5-dichloro-2-n-octylisothiazol- 3-one	64359-81-5	< 0.2
Diphenyl ketone	119-61-9	< 0.2

All concentrations are in percent by weight (kg) unless ingredient is a gas. Gas concentrations are in percent by volume (I).

4 First-aid measures

4. Filst-diu medsules	
Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. If ingestion of a large amount does occur, call a poison control center immediately.
Most important symptoms/effects, acute and delayed	May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from	During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire. and precautions for firefighters

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials. No unusual fire or explosion hazards noted.

6. Accidental release measures

Special protective equipment

equipment/instructions Specific methods

General fire hazards

the chemical

Fire fighting

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	This product is moderately soluble in water. Should not be released into the environment.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value
Diphenyl ketone (CAS 119-61-9)	TWA	0.5 mg/m3
Biological limit values	No biological exposure limits noted for	or the ingredient(s).
Appropriate engineering controls	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.	
Individual protection measures	s, such as personal protective equipm	nent
Eye/face protection	Use safety glasses, goggles, or face	shield to protect eyes.
Skin protection		
Hand protection	Wear appropriate chemical resistant supplier.	gloves. Suitable gloves can be recommended by the glove
Skin protection		
Other	Wear suitable protective clothing.	
Respiratory protection	In case of insufficient ventilation, wea	ar suitable respiratory equipment.
Thermal hazards	Wear appropriate thermal protective	clothing, when necessary.
General hygiene considerations	and before eating, drinking, and/or si	ene measures, such as washing after handling the material moking. Routinely wash work clothing and protective Contaminated work clothing should not be allowed out of the

9. Physical and chemical properties

-	
Appearance	Milky white to colored liquid.
Physical state	Liquid.
Form	Liquid.
Color	Various.
Odor	Slightly ammoniacal.
Odor threshold	Not available.
рН	7 - 10
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	Not available.
Evaporation rate	< 1 (n-BuAc=1)
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	> 1 (Air=1)
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Moderately soluble.
Partition coefficient (n-octanol/water)	Not available.

Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
VOC	47.26 - 48.35 g/L

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Strong acids.
Hazardous decomposition products	Carbon oxides. Metal oxides.

11. Toxicological information

Information on likely routes of exposure

information on intery routes of e	Aboon o		
Inhalation	Prolonged inhalation may be harmf	ful.	
Skin contact	May cause an allergic skin reaction.		
Eye contact	Direct contact with eyes may cause temporary irritation.		
Ingestion	Expected to be a low ingestion hazard.		
Symptoms related to the physical, chemical and toxicological characteristics	May cause an allergic skin reaction. Dermatitis. Rash.		
Information on toxicological effe	ects		
Acute toxicity	Not expected to be acutely toxic.		
Skin corrosion/irritation	Prolonged skin contact may cause	temporary irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause	e temporary irritation.	
Respiratory or skin sensitization	1		
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	May cause an allergic skin reaction	1.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	Inhalation of carbon black or titanium dioxide dust may cause cancer, however due to the physical form of the product, inhalation of dust is not likely. Diphenyl ketone has caused cancer in laboratory animals, however the relevance of this to humans is unknown.		
IARC Monographs. Overall	Evaluation of Carcinogenicity		
Carbon black (CAS 1333 Diphenyl ketone (CAS 11 Titanium dioxide (CAS 13	9-61-9) 2B 3463-67-7) 2B	Possibly carcinogenic to humans. Possibly carcinogenic to humans. Possibly carcinogenic to humans.	
NTP Report on Carcinogens	5		
Not listed. OSHA Specifically Regulate	d Substances (29 CFR 1910.1001-1	1053)	
Not regulated.			
Reproductive toxicity	This product is not expected to cau	use reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not an aspiration hazard.		
Chronic effects	Prolonged inhalation may be harmf	ful. Prolonged exposure may cause chronic effects.	
1250 AcryShield Exterior Semi-Gloss	Stock Colors 23 407 417		SDS US

12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	This product is moderately water soluble and may disperse in soil.
Other adverse effects	None known.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.		
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)			
Diphenyl ketone (CAS 119-61-9) 0.1 % One-Time Export Notification only. CERCLA Hazardous Substance List (40 CFR 302.4)			
Not listed. SARA 304 Emergency relea	se notification		
Not regulated. OSHA Specifically Regulate Not regulated.	d Substances (29 CFR 1910.1001-1053)		
Superfund Amendments and Reauthorization Act of 1986 (SARA) SARA 302 Extremely hazardous substance Not listed.			
SARA 311/312 Hazardous chemical	Yes		
Classified hazard categories	Respiratory or skin sensitization		
SARA 313 (TRI reporting) Not regulated.			
Other federal regulations			
Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Not regulated.			
C C	112(r) Accidental Release Prevention (40 CFR 68.130)		

Safe Drinking Water Act Not regulated. (SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Carbon black (CAS 1333-86-4) Titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

3-lodo-2-propynyl butyl carbamate (CAS 55406-53-6) Carbon black (CAS 1333-86-4) Titanium dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Carbon black (CAS 1333-86-4) Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Carbon black (CAS 1333-86-4) Titanium dioxide (CAS 13463-67-7)

California Proposition 65



WARNING: This product can expose you to chemicals including Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

United States & Puerto Rico Toxic Su	Ibstances Control Act (TSCA) Inventory	Yes	
Country(s) or region Inventor	ny name	On inventory (yes/no)*	
International Inventories			
Diphenyl ketone (CAS 119-61-9 Titanium dioxide (CAS 13463-6	9)		
Carbon black (CAS 1333-86-4)			
subd. (a))			
	als List. Safer Consumer Products Regulations (C	al. Code Regs, tit. 22, 69502.3,	
Lead (CAS 7439-92-1)	Listed: August 7, 2009 Listed: February 27, 1987		
Cadmium (CAS 7440-43-9) Ethylene oxide (CAS 75-21-8)	Listed: May 1, 1997 Listed: August 7, 2009		
•	-		
Lead (CAS 7439-92-1)	Listed: February 27, 1987 isted date/Male reproductive toxin.		
Ethylene oxide (CAS 75-21-8)	Listed: February 27, 1987		
California Proposition 65 - CRT: Listed date/Female reproductive toxin			
Methanol (CAS 67-56-1)	Listed: March 16, 2012		
Mercury (CAS 7439-97-6)	Listed: July 1, 1990		
Lead (CAS 7439-92-1)	Listed: February 27, 1987		
Ethylene oxide (CAS 75-21-8)	Listed: August 7, 2009		
Cadmium (CAS 7440-43-9)	Listed: May 1, 1997		
4-Methylpentan-2-one (CAS 10	8-10-1) Listed: March 28, 2014		
California Proposition 65 - CRT: L	isted date/Developmental toxin		
Nickel (CAS 7440-02-0)	Listed: October 1, 1989		
Methyloxirane (CAS 75-56-9)	Listed: October 1, 1988		
Lead (CAS 7439-92-1)	Listed: October 1, 1992		
Ethylene oxide (CAS 75-21-8)	Listed: July 1, 1987		
Ethylbenzene (CAS 100-41-4)	Listed: May 3, 2011 Listed: June 11, 2004		
Dibromoacetonitrile (CAS 3252	,,		
Arsenic (CAS 7440-38-2) Cadmium (CAS 7440-43-9)	Listed: February 27, 1987 Listed: October 1, 1987		
4-Methylpentan-2-one (CAS 10			
1,4-Dioxane (CAS 123-91-1)	Listed: January 1, 1988		

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date

26-June-2018

Revision date

_

Disclaimer

01 Health: 2 Flammability: 1 Physical hazard: 0

Kelly-Moore Paint Co., Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.